



101P+ TRMS

TRMS, Auto Ranging, 3¾ Digits 4000 Counts LCD with Backlight, APO, Capacitance, REL Δ, Frequency

Ranges

DC Voltage 40 / 400mV / 4 / 40 / 400 / 1000V

Accuracy ± (0.5% rdg + 3 dgt)

AC Voltage 40 / 400mV / 4 / 40 / 400 / 750V

Accuracy ± (1.0% rdg + 3 dgt)

AC Response 10Hz ~ 1KHz

DC Current 400 / 4000µA / 40 / 400mA / 4 / 10A

Accuracy ± (0.8% rdg + 3 dgt)

on 400 / 4000µA, 40 / 400mA

± (1.0% rdg + 3 dgt)

on 4 / 10A

AC Current 400 / 4000µA / 40 / 400mA / 4 / 10A

Accuracy ± (1.0% rdg + 3 dgt)

on 400 / 4000µA, 40 / 400mA

± (1.2% rdg + 3 dgt)

on 4 / 10A

AC Response 10Hz ~ 1KHz

Resistance 400Ω / 4 / 40 / 400KΩ / 4 / 40MΩ

Accuracy ± (0.5% rdg + 3 dgt)

on all ranges except

± (1.0% rdg + 3 dgt)

on 400Ω

± (1.5% rdg + 3 dgt)

on 40MΩ

Capacitance 4.000 / 40.00 / 400.0nF / 4.000 / 40.00 / 400.0µF / 4.000mF

Accuracy ± (3.5% rdg + 4 dgt)

on all ranges except

± (5.0% rdg + 5 dgt) on 4mF

± (5.0% rdg + 50 dgt)

on 4.000nF, 40.00nF

Frequency 4.000 / 40.00 / 400.0Hz / 4.000 / 40.00 / 400.0KHz / 4.000MHz

Sensitivity 1V to 36V AC

Accuracy ±(1.5% rdg + 3 dgt)

Measuring Category CAT III 600V, CAT II 1000V

SP Function Diode Test, Audible Continuity, Data Hold

Power Two 1.5V 'AAA' Battery

Low Battery '⚡' is indicated

Battery Life 200 hours typical

Dimensions 142 x 68 x 36mm (approx.)

Weight 173gms Including Battery (approx.)

Accessories One Pair of Test Leads, Battery (installed), Carrying Case & Instruction Manual