



DMM 603+



DMM 830L



DT 2727+

<p>3½ Digit 2000 Counts, Audible Continuity, Diode Test, hFE Test, Backlight, Data Hold & APO</p> <p>Ranges</p> <p>DC Voltage 200mV/2/20/200/1000V Accuracy ±(0.5% rdg + 3 dgt) 200mV ±(0.8% rdg + 5 dgt) 2V, 20V, 200V ±(1.0% rdg + 5 dgt) 1000V</p> <p>AC Voltage 200/750V [45~450Hz] Accuracy ± [2.0% rdg + 10 dgt]</p> <p>DC Current 200 µA/2mA/20mA/ 200mA/20A Accuracy ±(1.8% rdg + 2 dgt) 200µA, 2mA, 20mA ±(2.0% rdg + 2 dgt) 200mA ±(2.0% rdg + 10 dgt) 20A</p> <p>AC Current 20mA/200mA/20A [45~450Hz] ±(1.8% rdg + 2 dgt) 20mA ±(2.0% rdg + 2 dgt) 200mA ±(2.0% rdg + 10 dgt) 20A</p> <p>Resistance 200Ω/2kΩ/200kΩ/20MΩ 200MΩ Accuracy ±(1.2% rdg + 8 dgt) on all ranges, except ±(1%rdg+10dgt) on 200Ω</p> <p>Sp. Function Audible Continuity, Diode Test, hFE Test</p> <p>Power Two 1.5V "AAA" Battery</p> <p>Low Battery "⚡" is indicated</p> <p>Battery Life 200 hours typical</p> <p>Dimensions 160 x 76 x 32mm (approx.)</p> <p>Weight 155gms Including Battery (approx)</p> <p>Accessories One Pair of Test Leads, Battery [installed], Instruction Manual</p>	<p>3½ Digit 2000 Counts, Audible Continuity, Diode Test, hFE Test, Backlight & Data Hold</p> <p>Ranges</p> <p>DC Voltage 200mV/2/20/200/600V Accuracy ±(0.5% rdg + 3 dgt) 200mV ±(0.8% rdg + 5 dgt) 2V, 20V, 200V ±(1.0% rdg + 5 dgt) 600V</p> <p>AC Voltage 200/600V [45~450Hz] Accuracy ± [2.0% rdg + 10 dgt]</p> <p>DC Current 200 µA/2mA/20mA/ 200mA/10A Accuracy ±(1.8% rdg + 2 dgt) 200µA, 2mA, 20mA ±(2.0% rdg + 2 dgt) 200mA ±(2.0% rdg + 10 dgt) 10A</p> <p>Resistance 200Ω/2kΩ/20kΩ/200kΩ/ 2MΩ Accuracy ±(1.0%rdg+4dgt) on all ranges, except ±(1%rdg+10dgt) on 200Ω</p> <p>Sp. Function Audible Continuity, Diode Test, hFE Test</p> <p>Power One 9V Battery</p> <p>Low Battery "⚡" is indicated</p> <p>Battery Life 200 hours typical</p> <p>Dimensions 145 x 76 x 43mm (approx.)</p> <p>Weight 207gms Including Battery (approx)</p> <p>Accessories One Pair of Test Leads, Battery [installed], Instruction Manual & Holster</p>	<p>400A AC (TRMS)</p> <p>3½ Digit, 1999 Counts, NCV (Buzzer & EF Strength), Data Hold, Backlight & APO</p> <p>Ranges</p> <p>AC Current ^{TRMS} 400A Accuracy ± [2.5%rdg+ 10dgt] (50-60Hz) Overload 400A AC max. for 1 min.</p> <p>AC Voltage ^{TRMS} 600V Accuracy ± (1.2%rdg+ 8dgt) (50-60Hz)</p> <p>DC Voltage 600V Accuracy ± (1.0%rdg+ 5dgt)</p> <p>Resistance 2MΩ Accuracy ± (1.5%rdg + 3dgt)</p> <p>Sp. Function Audible Continuity, Diode Test</p> <p>Power Two 1.5V "AAA" Battery</p> <p>Battery Life 200 Hours Typical</p> <p>Low Battery "⚡" is indicated</p> <p>Dimension 175 x 60 x 34 mm (approx.)</p> <p>Weight 150gms Including Battery (approx.)</p> <p>Accessories One Pair of Test Leads, Carrying Case, Battery [installed] Instruction Manual</p> <p>Jaw Opening Cable Dia. 23mm (max.)</p> <div data-bbox="1053 1617 1260 1974"> </div> <p>Pair of Test Leads Suitable for DMM / DTT (Optional)</p> <p>Model : TL-DMM / DTT (N) Category : CAT III Max. Voltage : 1000V Max. Current : 10A (Upto 1 min.) Length : 1000mm (approx.)</p>
--	---	--